

GUIDELINE FOR RESIDENTIAL SAFETY INSPECTION (CCO)

(THIS IS ONLY A SAMPLE OF ITEMS THE INSPECTOR MAY CHECK FOR)

(PLEASE GO THROUGH THE LIST)

A REPRESENTATIVE MUST BE ON LOCATION

HOUSE #'s (Arabic lettering, 3 inches mounted to front wall or porch and 30 inches above ground)

PASS FAIL

SMOKE ALARMS (1 ON EACH FLOOR AND IN EACH BEDROOM) Ten Year Sealed battery-powered single station smoke alarms shall be installed where no smoke alarms exit or when replacing similar battery-powered single station smoke alarms. A/C powered single or multi station smoke alarms not be replaced with battery-powered smoke alarms.

PASS FAIL

CARBON MONOXIDE DETECTOR (on each floor)

PASS FAIL

FIRE EXTINGUISHER (INSTALLED 5 FT. FROM GROUND, MOUNTED ON THE WALL, WITHIN 10 FT OF THE KITCHEN IN VIEW OF PUBLIC) (MOUNTED WAIST LEVEL IS ACCEPTED) MUST BE A 2A/10BC FIRE EXTINGUISHER, not to exceed 10lbs.

PASS FAIL

SIDE WALKS & DRIVEWAYS (No cracks and no unevenness) (no skim coating/no ramping)

PASS FAIL

PORCH OR DECK (front & rear) (Must be well maintained and sturdy)

PASS FAIL

WINDOWS OPERABLE & IN DECENT CONDITION

PASS FAIL

RAILING ON STAIRS (4 steps or more must have a firmly secured railing)

PASS FAIL

WATER CHECK (flush, drains, hot water)

PASS FAIL



LIGHT SWITCHES & RECEPTACLES (must have covers on them)

PASS FAIL

GENERAL CONDITION (no holes in walls, floors and ceiling and painted)

PASS FAIL

SUMP PUMP MUST NOT BE TIED INTO SEWER SYSTEM

N/A PASS FAIL

CONDITION OF YARD & PROPERTY (grass cut and yard trimmed etc.)

PASS FAIL

SECONDARY POWER SOURCE (solar power or generators) AS OF 2/3/25 LABELS MUST BE ON ELECTRIC PANELS AND ELECTRIC MEETERS advising secondary power source

N/A PASS FAIL

SOLAR PANELS AND ELECTRIC VEHICLE CHARGES MUST HAVE BEEN PERMITED

N/A PASS FAIL

VIOLATIONS (other than above)

PASS FAIL

PASS FAIL

ANY OPEN PERMITS MUST BE CLOSED/ FINALIZED